

Soudaprim DP

Revision: 8/02/2021

Page 1 from 2

Technical data

Basis	Synthetic dispersion
Consistency	Fluid
Density**	Ca. 1,01 g/ml
Consumption*	0.1 - 0.2 L/ m ² for 1 coat
Application temperature	5 °C → 35 °C
pH level	8,0 → 9,0

* These values may vary depending on environmental factors such as temperature, moisture, and type of substrates. ** This information relates to fully cured product.

Product description

Soudaprim DP is a primer for liquid waterproofing membranes. Developed for porous substrates. Soudaprim DP fully penetrates the substrate and this results in better adhesion of the membrane.

Properties

- Ready to use (no mixing required)
- Fast drying
- Solvent free
- Very easy to apply

Applications

- As a primer in the application of a liquid waterproofing membrane
- All porous surfaces.
- Humid rooms like bathroom, shower, kitchen, ...

Packaging

Colour: pink

Packaging: 1 L, 5 L

Shelf life

At least 12 months in the original closed packing and if stored in a dry place, at temperatures between 5°C and 30°C. Protect from damage, frost and direct sunlight. Also during transport.

Substrates

Substrates: Porous surfaces such as stone, concrete, plaster, wood.

It is recommended to perform a preliminary compatibility test on any surface.

Nature: solid, free from dust, oil, grease, sand and other contaminants

Surface preparation: No pretreatment required.

Application method

Application method: Soudaprim DP can be applied with a paint roller or brush. Apply the primer in 1 coat, directly from the package, without diluting. In the case of very porous and highly absorbent substrates, apply a second coat. Wait at least 2 hours before applying the liquid membrane.

Health- and Safety Recommendations

Take the usual labour hygiene into account. Always wear gloves and goggles. Use only in well-ventilated areas. Consult label for more information.

Remark: This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. In every case it is recommended to carry out preliminary experiments. Soudal reserves the right to modify products without prior notice.

Soudaprim DP

Revision: 8/02/2021

Page 2 from 2

Remarks

- Substrates must not be exposed to constant submersion or rising damp
- Do not apply when relative humidity exceeds 75%

Liability

The content of this technical data sheet is the result of tests, monitoring and experience. It is general in nature and does not constitute any liability. It is the responsibility of the user to determine by his own tests whether the product is suitable for the application.

Remark: This technical data sheet replaces all previous versions. The directives contained in this documentation are the result of our experiments and of our experience and have been submitted in good faith. Because of the diversity of the materials and substrates and the great number of possible applications which are out of our control, we cannot accept any responsibility for the results obtained. Since the design, the quality of the substrate and processing conditions are beyond our control, no liability under this publication is accepted. In every case it is recommended to carry out preliminary experiments. Soudal reserves the right to modify products without prior notice.